

Black Rock Speedway

Four Cylinder Enduro Division

- ❖ Blackrock Speedway reserves the right to tear down the top three(3) and or any car at random.
- ❖ TECH WILL INCLUDE: Removal of cyl. head, Intake and Exhaust Manifolds and oil pan.
- ❖ The frame and suspension must remain completely stock original.
- ❖ ENGINE: Must remain stock as manufactured and meet all OEM specifications for the year, make and model used.
- ❖ **NO** porting, polishing, acid dipping or port matching of any components.
- ❖ All Cars must be 4-cylinder non-turbo charged - no pick-ups, jeeps, or convertibles
- ❖ Only pump gas is permitted
- ❖ The stock carburetor / fuel injection system for that make and model must be used
- ❖ The stock transmission for that make and model must be used and unaltered.
- ❖ The battery must remain under the hood
- ❖ The stock unaltered rear end for that make and model must be used
- ❖ All season passenger tires only are permitted. **NO winter tires allowed.** Wheel and tires must be of same size. Stock wheels only with a maximum of 6" wide, and a maximum of 14" tall. **Reinforcement of the right front wheel is recommended**
- ❖ Original gas tanks must remain in stock location, it is recommended that a skid plate be installed to protect the fuel tank: if your car has a plastic fuel tank

mounted under the body in front of the rear end. If you want to use a fuel cell, it must be located in the trunk. Secured with steel straps. Two from side to side and two front to back. Trunk floor must remain stock, no lowering of the fuel cells.

Driver's seat must be an approved aluminum racing seat, and have a minimum 4 point racing harness.

- ❖ A 4 point roll cage is mandatory. Must have a min. of (2) 1 ½" Horizontal door bars to protect the driver on the left side.

RECOMMENDATIONS:

(6 point roll cage.

Diagonal brace or "X" in the cage behind driver.

Halo support bar above driver.

Vertical supports between drivers horizontal door bars.

Racing seat mounted directly to roll cage).

- ❖ The driver's door must be securely fastened.
- ❖ All glass and plastic trim must be removed from the outside of the body. All headlights, taillights, marker lights, grills, mirrors, door handles, and any miscellaneous exterior plastic must be removed. Windshield may remain.
- ❖ It is recommended that all drivers wear a clean one piece driver's uniform with nomex underwear, head sock, gloves, foot socks and shoes.
- ❖ It is mandatory that as a minimum all drivers wear CARHARTT unlined denim bib overalls R08 and jacket J12DST or equivalent 100% cotton work wear. No polyester may be present.
- ❖ A drivers side window net is mandatory
- ❖ All drivers must wear a 2000 or newer SNELL approved full face helmet
- ❖ A neck brace is mandatory.

- ❖ The driver's floor pan must be complete, no holes of any kind
- ❖ The exhaust must exit behind the driver's compartment
- ❖ Cars must have a minimum 20" high number

A cockpit mounted fire extinguisher is highly recommended

- ❖ No suggestive language, symbols and/or numbers are permitted on the cars.
 - ❖ No communication device of any kind in car
 - ❖ At anytime Black Rock Speedway may claim the racecar. The claim amount is \$1000.00. All safety equipment may be retained by the driver.
 - ❖ Anything not covered in these rules will be up to the discretion of the track officials, their decision is final.
-
- ❖ In the event of a serious injury Black Rock Speedway reserves the right to impound any car involved in the accident